

**DECLARATION OF PERFORMANCE**  
**No.069A.00**



1. Name and code of the product:

Product: MAXEPOX BOND

Batch: See packaging

2. Name and contact address of the manufacturer or importer or distributor:

Name: DRIZORO, SAU

Contact address: C/Primavera 50-52.P.Ind. Las Monjas. 28850-Torrejón de Ardoz. (Madrid, Spain)

3. Intended use:

TWO COMPONENT EPOXY BASED STRUCTURAL BONDING AGENT.

4. System of assessment and verification of constancy of performance: System 4

5. Notified body:

Name and identification number: APPLUS, 0370

Notified task: Initial type testing

System of assessment: System 4

6. Declared performance

ZA 1a. Plate bonding method

Essential Characteristics	Performance	Harmonised Technical Specification
SHRINKAGE	< 0,1%	EN 1504-4:2006
WORKABILITY TIME	60 min	
ELASTICITY MODULUS	13557 N/mm <sup>2</sup>	
THERMAL EXPANSION COEFFICIENT	86,5 µm/m°C	
GLASS TRANSITION TEMPERATURE	>40 °C	
DURABILITY	PASS	
DANGEROUS SUBSTANCES	Comply 5.4	

ZA 1b.Mortar or concrete bonding method

Essential Characteristics	Performance	Harmonised Technical Specification
ADHERENCE	PASS	EN 1504-4:2006
SHEAR STRENGTH	11,7 N/mm <sup>2</sup>	
COMPRESSION STRENGTH	65 N/mm <sup>2</sup>	
SHRINKAGE	< 0,1%	
WORKABILITY TIME	60 min	
SENSIBILITY TO WATER	PASS	
ELASTICITY MODULUS	13557 N/mm <sup>2</sup>	
THERMAL EXPANSION COEFFICIENT	86,5 µm/m°C	
GLASS TRANSITION TEMPERATURE	>40 °C	
DURABILITY	PASS	
DANGEROUS SUBSTANCES	Comply 5.4	

- The performance of the product identified in point 1 is in conformity with the declared performance in point 6.
- This declaration of performance is issued under the sole responsibility of the manufacturer, importer or distributor identified in point 2.
- Signed for and behalf of the manufacturer, or importer or distributor by:



Mr. Francisco Rodríguez Álvarez.  
 Director of Quality and Environment.

Torrejón de Ardoz, 12<sup>th</sup> September, 2014