(in accordance with Regulation (EU) 2015/830)

# **MAXEPOX MORTER (Comp. A)**

Version: 7 Page 1 of 10
Revision date: 21/01/2017 Print date: 21/01/2017



## SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

#### 1.1 Product identifier.

Product Name: MAXEPOX MORTER (Comp. A)

## 1.2 Relevant identified uses of the mixture and uses advised against.

**Epoxy Coating** 

## Uses advised against:

Uses other than those recommended.

### 1.3 Details of the supplier of the safety data sheet.

Company: DRIZORO, S.A.U.

Address: C/ Primavera, 50 - 52 Parque Industrial Las Monjas

City: 28850 Torrejón de Ardoz

 Province:
 Madrid (Spain)

 Telephone:
 +34 91 676 66 76

 Fax:
 +34 91 675 11 31

 E-mail:
 info@drizoro.com

1.4 Emergency telephone number: +34 91 676 66 76 (Only available during office hours)

### **SECTION 2: HAZARDS IDENTIFICATION.**

IRRITANT PREPARATION. Splatters in the eyes can cause irritation.

## 2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008:

Aquatic Chronic 2: Toxic to aquatic life with long lasting effects.

Eye Irrit. 2 : Causes serious eye irritation. Muta. 2 : Suspected of causing genetic defects.

Skin Irrit. 2: Causes skin irritation.

Skin Sens. 1: May cause an allergic skin reaction.

## 2.2 Label elements.

# Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:







# Signal Word:

# Warning

H statements:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H341 Suspected of causing genetic defects.
 H411 Toxic to aquatic life with long lasting effects.

P statements:

P201 Obtain special instructions before use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

(in accordance with Regulation (EU) 2015/830)

# **MAXEPOX MORTER (Comp. A)**



DRIZOR

 Version: 7
 Page 2 of 10

 Revision date: 21/01/2017
 Print date: 21/01/2017

P321 Specific treatment (see ... on this label).

P391 Collect spillage.

P501 ispose of contents / container in accordance with local legislation in force

**EUH statements:** 

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Contains:

epoxy resin (number average molecular weight ≤ 700),reaction product: bisphenol-A-(epichlorhydrin)

[(tolyloxy)methyl]oxirane,cresyl glycidyl ether (Mixture of isomers)

#### 2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.**

IRRITANT PREPARATION. Splatters in the eyes can cause irritation.

#### 3.1 Substances.

Not Applicable.

#### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

			(*)Classification - Regulation (EC) No 1272/2008	
Identifiers	Name	Concentrate	Classification	specific concentration limit
Index No: 603-074- 00-8 CAS No: 25068-38-6 EC No: 500-033-5 Registration No: 01- 2119456619-26-XXXX	epoxy resin (number average molecular weight ≤ 700),reaction product: bisphenol-A-(epichlorhydrin)	25 - 100 %	Aquatic Chronic 2, H411 - Eye Irrit. 2, H319 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	Eye Irrit. 2, H319: C ≥ 5 % Skin Irrit. 2, H315: C ≥ 5 %
Index No: 603-056- 00-X CAS No: 26447-14-3 EC No: 247-711-4	[(tolyloxy)methyl]oxirane,cresyl glycidyl ether (Mixture of isomers)	2.5 - 10 %	Aquatic Chronic 2, H411 - Muta. 2, H341 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-

<sup>(\*)</sup> The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

# **SECTION 4: FIRST AID MEASURES.**

IRRITANT PREPARATION. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

### 4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

### Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

## Eye contact.

If wearing contact lenses, remove them. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

## Skin contact.

(in accordance with Regulation (EU) 2015/830)

# **MAXEPOX MORTER (Comp. A)**



Construction Products

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. **NEVER** use solvents or thinners.

#### Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. **NEVER** induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate. Can cause allergic reactions.

Harmful Product, prolonged exposure due to inhalation may cause anaesthetic effects and the need for immediate medical assistance.

## 4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

### **SECTION 5: FIREFIGHTING MEASURES.**

The product does not present any particular risk in case of fire.

#### 5.1 Extinguishing media.

## Recommended extinguishing methods.

Extinguisher powder or  $CO_2$ . In case of more serious fires, also alcohol-resistant foam and water spray. Do not use a direct stream of water to extinguish.

### 5.2 Special hazards arising from the mixture.

## Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

## 5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

### Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and gloves.

# **SECTION 6: ACCIDENTAL RELEASE MEASURES.**

## 6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

### 6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

# 6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate decontaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

### 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

(in accordance with Regulation (EU) 2015/830)

# **MAXEPOX MORTER (Comp. A)**



 Version: 7
 Page 4 of 10

 Revision date: 21/01/2017
 Print date: 21/01/2017

### **SECTION 7: HANDLING AND STORAGE.**

### 7.1 Precautions for safe handling.

For personal protection, see section 8. Never use pressure to empty the containers. They are not pressure-resistant containers. In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Keep the product in containers made of a material identical to the original.

### 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III)::

		Qualifying quantity (tonnes) for the application of	
Code	Description	Lower-tier requirements	Upper-tier requirements
E2	ENVIRONMENTAL HAZARDS - Hazardous to the Aquatic Environment in Category Chronic 2	200	500

### 7.3 Specific end use(s).

Not available.

### **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.**

### 8.1 Control parameters.

The product does NOT contain substances with Professional Exposure Environmental Limit Values. The product does NOT contain substances with Biological Limit Values. Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
epoxy resin (number average molecular weight ≤	DNEL	Inhalation, Long-term, Systemic effects	12,25
700),reaction product: bisphenol-A-(epichlorhydrin)	(Workers)		(mg/m³)
N. CAS: 25068-38-6			
N CE: 500-033-5	1		

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

## 8.2 Exposure controls.

### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %		
Uses:	Epoxy Coating		
Breathing protection:			
If the recommende	ed technical measures are observed, no individual protection equipment is necessary.		
Hand protection:			
PPE: Characteristics:	Protective gloves. «CE» marking, category II.		
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420		
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives		

(in accordance with Regulation (EU) 2015/830)

# **MAXEPOX MORTER (Comp. A)**

 Version: 7
 Page 5 of 10

 Revision date: 21/01/2017
 Print date: 21/01/2017



Observations:	Gloves should be of the appropriate size and fit Always use with clean, dry hands.	the user's hand well	, not being too loose	or too tight.
Material:	PVC (polyvinyl chloride) Breakthrough time (min.):	> 480	Material thickness (mm):	0,35
Eye protection:				
PPE:	Face shield.			
Characteristics:	«CE» marking, category II. Face and eye protector against splashing liquid.			
CEN standards:	EN 165, EN 166, EN 167, EN 168			
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly.			
Observations:	Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame.			
Skin protection:				
PPE:	Protective clothing.			
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.			
CEN standards:	EN 340			
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.			
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.			
PPE:	Work footwear.			
Characteristics:	«CE» marking, category II.			
CEN standards:	EN ISO 13287, EN 20347			
Maintenance:	This product adapts to the first user's foot shap not be used by other people.		, 5	,
Observations:	Work footwear for professional use includes pro injury resulting from an accident	otection elements aim	ned at protecting use	rs against any

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.**

# 9.1 Information on basic physical and chemical properties.

Appearance: Paste with characteristic colour and odour

Colour: N.A./N.A. Odour:N.A./N.A.

Odour threshold: N.A./N.A.

pH:N.A./N.A.

Melting point: N.A./N.A. Boiling Point: N.A./N.A. Flash point: N.A./N.A. Evaporation rate: N.A./N.A.

Inflammability (solid, gas): N.A./N.A. Lower Explosive Limit: N.A./N.A. Upper Explosive Limit: N.A./N.A. Vapour pressure: N.A./N.A. Vapour density:N.A./N.A. Relative density:1,15 g/cm<sup>3</sup> Solubility: N.A./N.A. Liposolubility: N.A./N.A.

Hydrosolubility: N.A./N.A.
Partition coefficient (n-octanol/water): N.A./N.A.

Auto-ignition temperature: N.A./N.A. Decomposition temperature: N.A./N.A.

Viscosity: N.A./N.A.

Explosive properties: N.A./N.A. Oxidizing properties: N.A./N.A.

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

# 9.2 Other information.

(in accordance with Regulation (EU) 2015/830)

# **MAXEPOX MORTER (Comp. A)**

Version: 7

Revision date: 21/01/2017



Page 6 of 10 Print date: 21/01/2017

Pour point: N.A./N.A. Blink: N.A./N.A.

Kinematic viscosity: N.A./N.A.

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

# **SECTION 10: STABILITY AND REACTIVITY.**

### 10.1 Reactivity.

The product does not present hazards by their reactivity.

### 10.2 Chemical stability.

Unstable in contact with:

- Acids.
- Bases.
- Oxidizing agents.

### 10.3 Possibility of hazardous reactions.

In certain conditions this may cause a polymerization reaction.

### 10.4 Conditions to avoid.

Avoid the following conditions:

- Heating.
- High temperature.
- Contact with incompatible materials.

### 10.5 Incompatible materials.

Avoid the following materials:

- Acids.
- Bases.
- Oxidizing agents.

### 10.6 Hazardous decomposition products.

Depending on conditions of use, can be generated the following products:

- COx (carbon oxides).
- Organic compounds.

# **SECTION 11: TOXICOLOGICAL INFORMATION.**

Based on the properties of the epoxy components, and keeping in mind the toxicological data on similar preparations, this preparation can sensitise and irritate the skin, eyes, and respiratory tract.

The low molecular weight epoxy components are irritants to the eyes, mucous membranes, and skin. Repeated contact with the skin can lead to its irritation or sensitisation, possibly with accentuated autosensitisation to other epoxies.

IRRITANT PREPARATION. Splatters in the eyes can cause irritation.

IRRITANT PREPARATION. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

### 11.1 Information on toxicological effects.

There are no tested data available on the product.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

a) acute toxicity:

Not conclusive data for classification.

b) skin corrosion/irritation;

Product classified:

Skin irritant, Category 2: Causes skin irritation.

(in accordance with Regulation (EU) 2015/830)

# **MAXEPOX MORTER (Comp. A)**

•

 Version: 7
 Page 7 of 10

 Revision date: 21/01/2017
 Print date: 21/01/2017

DRIZOR

Construction Products



Product classified:

Eye irritation, Category 2: Causes serious eye irritation.

### d) respiratory or skin sensitisation;

Product classified:

Skin sensitiser, Category 1: May cause an allergic skin reaction.

#### e) germ cell mutagenicity;

Product classified:

Mutagen, Category 2: Suspected of causing genetic defects.

#### f) carcinogenicity;

Not conclusive data for classification.

### g) reproductive toxicity;

Not conclusive data for classification.

#### h) STOT-single exposure;

Not conclusive data for classification.

### i) STOT-repeated exposure;

Not conclusive data for classification.

### j) aspiration hazard;

Not conclusive data for classification.

# **SECTION 12: ECOLOGICAL INFORMATION.**

### 12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

### 12.2 Persistence and degradability.

No information is available about persistence and degradability of the product.

# 12.3 Bioaccumulative potencial.

No information is available regarding the bioaccumulation of the substances present.

# 12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

### 12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

# **SECTION 13 DISPOSAL CONSIDERATIONS.**

## 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

# **SECTION 14: TRANSPORT INFORMATION.**

(in accordance with Regulation (EU) 2015/830)

# **MAXEPOX MORTER (Comp. A)**

Version: 7

Revision date: 21/01/2017 Print date: 21/01/2017

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA

for air transport.

**Land:** Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

<u>Sea</u>: Transport by ship: IMDG. Transport documentation: Bill of lading <u>Air</u>: Transport by plane: ICAO/IATA. Transport document: Airway bill.

**14.1 UN number.** UN No: UN3082

### 14.2 UN proper shipping name.

Description:

ADR: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT  $\leq$  700), REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN) / [(TOLYLOXY)METHYL]OXIRANE, CRESYL GLYCIDYL ETHER (MIXTURE OF ISOMERS)), 9, PG III, (E) IMDG: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT  $\leq$  700), REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN) / [(TOLYLOXY)METHYL]OXIRANE, CRESYL GLYCIDYL ETHER (MIXTURE OF ISOMERS)), 9, PG III, MARINE POLLUTANT ICAO: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT  $\leq$  700), REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN) /

[(TOLYLOXY)METHYL]OXIRANE,CRESYL GLYCIDYL ETHER (MIXTURE OF ISOMERS)), 9, PG III

**14.3 Transport hazard class(es).** Class(es): 9

### 14.4 Packing group.

Packing group: III

### 14.5 Environmental hazards.

Marine pollutant: Yes



Dangerous for the environment

## 14.6 Special precautions for user.

Labels: 9



Hazard number: 90 ADR LQ: 5 L IMDG LQ: 5 L ICAO LQ: 30 kg B

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR. Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-A,S-F Proceed in accordance with point 6.

## 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.


The product is not transported in bulk.

Construction Products

Page 8 of 10

(in accordance with Regulation (EU) 2015/830)

# **MAXEPOX MORTER (Comp. A)**





DRIZOR

### **SECTION 15: REGULATORY INFORMATION.**

This information is shown on the current Safety Data Sheet for the Preparation.

## 15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC)

VOC content (p/p): 0 % VOC content: 0 g/l

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): E2

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

### 15.2 Chemical safety assessment.

There has been no evaluation a chemical safety assessment of the product.

### **SECTION 16: OTHER INFORMATION.**

Complete text of the H phrases that appear in section 3:

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H341 Suspected of causing genetic defects.
H411 Toxic to aquatic life with long lasting effects.

### Classification codes:

Aquatic Chronic 2: Chronic effect to the aquatic environment, Category 2

Eye Irrit. 2 : Eye irritation, Category 2 Muta. 2 : Mutagen, Category 2 Skin Irrit. 2 : Skin irritant, Category 2 Skin Sens. 1 : Skin sensitiser, Category 1

Sections changed compared with the previous version:

1,2,4,7,14,16

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

CEN: European Committee for Standardization.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be

considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not

anticipated.

PPE: Personal protection equipment.
IATA: International Air Transport Association.
ICAO: International Civil Aviation Organization.

IMDG: International Maritime Code for Dangerous Goods.

(in accordance with Regulation (EU) 2015/830)

# **MAXEPOX MORTER (Comp. A)**

Version: 7 Page 10 of 10 Revision date: 21/01/2017 Print date: 21/01/2017

DRIZOR

**Construction Products** 

RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data: http://eur-lex.europa.eu/homepage.html

http://echa.europa.eu/ Regulation (EU) 2015/830. Regulation (EC) No 1907/2006. Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.