(in accordance with Regulation (EU) 2015/830)

MAXURETHANE FOAM CAN



Version: 0

Revision date: 27/02/2017

Page 1 of 10 Print date: 27/02/2017

SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name:

MAXURETHANE FOAM CAN

1.2 Relevant identified uses of the mixture and uses advised against.

Polyurethane expanding foam for fixing and sealing elements in building

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company:	DRIZORO, S.A.U.
Address:	C/ Primavera, 50 - 52 Parque Industrial Las Monjas
City:	28850 Torrejón de Ardoz
Province:	Madrid (Spain)
Telephone:	+34 91 676 66 76
Fax:	+34 91 675 11 31
E-mail:	info@drizoro.com

1.4 Emergency telephone number: +34 91 676 66 76 (Only available during office hours; Monday-Friday; 08:00-18:00)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008: Carc. 2 : Suspected of causing cancer. Eye Irrit. 2 : Causes serious eye irritation. Lact. : May cause harm to breast-fed children. Resp. Sens. 1 : May cause allergy or asthma symptoms or breathing difficulties if inhaled. STOT RE 2 : May cause damage to organs through prolonged or repeated exposure. STOT SE 3 : May cause respiratory irritation. Skin Irrit. 2 : Causes skin irritation. Aquatic Chronic 4 : May cause long lasting harmful effects to aquatic life. Acute Tox. 4 : Harmful if inhaled. Aerosol 1 : Pressurised container: May burst if heated.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008: Pictograms:



Signal Word:

Danger

H statements: H315 Causes skin irritation. H319 Causes serious eye irritation. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated. Harmful if inhaled. H332

(in accordance with Regulation (EU) 2015/830)

MAXURETHANE FOAM CAN

Version: 0

Revision date: 27/02/2017



Page 2 of 10 Print date: 27/02/2017

H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H362	May cause harm to breast-fed children.
H373	May cause damage to organs through prolonged or repeated exposure.
H413	May cause long lasting harmful effects to aquatic life.
statements:	
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P263	Avoid contact during pregnancy/while nursing.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P271	Use only outdoors or in a well-ventilated area.
P305+P351+P	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and
easy to do. Co	ntinue rinsing.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P302+P352	IF ON SKIN: Wash with plenty of water/
P501	ispose of contents / container in accordance with local legislation in force

EUH statements:

EUH204 Contains isocyanates. May produce an allergic reaction.

Contains:

Ρ

Polymeric diphenylmethane diisocyanate

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

			(*)Classification No 127	- Regulation (EC) 2/2008
Identifiers	Name	Concentrate	Classification	specific concentration limit
CAS No: 9016-87-9	Polymeric diphenylmethane diisocyanate	20 - 75 %	Carc. 2, H351 - Eye Irrit. 2, H319 - Resp. Sens. 1, H334 - STOT RE 2, H373 - STOT SE 3, H335 - Skin Irrit. 2, H315	-
Index No: 601-003- 00-5 CAS No: 74-98-6 EC No: 200-827-9 Registration No: 01- 2119486944-21-XXXX	propane	2.5 - 25 %	Flam. Gas 1, H220 - Press. Gas,	-
Index No: 602-095- 00-X CAS No: 85535-85-9 EC No: 287-477-0 Registration No: 01- 2119519269-33-XXXX	alkanes, C14-17, chloro,chlorinated paraffins, C14-17	2.5 - 25 %	Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Lact., H362	-

(in accordance with Regulation (EU) 2015/830)

MAXURETHANE FOAM CAN



Version: 0

Revision date: 27/02/2017

Page 3 of 10 Print date: 27/02/2017

-			
tris(2-chloro-1-methylethyl) phosphate	1 - 25 %	Acute Tox. 4, H302	-
[1] butane (Mixture of isomers)	2.5 - 10 %	Flam. Gas 1, H220 - Press. Gas,	-
[1] dimethyl ether	0 - 2.5 %	Flam. Gas 1, H220 - Press. Gas,	-
	[1] butane (Mixture of isomers) [1] dimethyl ether	[1] butane (Mixture of isomers) 2.5 - 10 %	tris(2-chloro-1-methylethyl) phosphate1 - 25 %H302[1] butane (Mixture of isomers)2.5 - 10 %Flam. Gas 1, H220 - Press. Gas,[1] dimethyl ether0 - 2.5 %Flam. Gas 1, H220 - Press. Gas,

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

[1] Substance with a Community workplace exposure limit (see section 8.1).

SECTION 4: FIRST AID MEASURES.

IRRITANT PREPARATION. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

If wearing contact lenses, remove them. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. **NEVER** use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. **NEVER** induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate. Can cause allergic reactions.

Harmful Product, prolonged exposure due to inhalation may cause anaesthetic effects and the need for immediate medical assistance.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

SECTION 5: FIREFIGHTING MEASURES.

The product is Extremely inflammable, it can cause or considerably worsen a fire, the necessary prevention measures should be taken and risks avoided. In case of fire, the following measures are recommended:

5.1 Extinguishing media.

Recommended extinguishing methods.

(in accordance with Regulation (EU) 2015/830)

MAXURETHANE FOAM CAN



Print date: 27/02/2017

Version: 0

Revision date: 27/02/2017

Extinguisher powder or CO_2 . In case of more serious fires, also alcohol-resistant foam and water spray. Do not use a direct stream of water to extinguish.

5.2 Special hazards arising from the mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and gloves.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes.For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate decontaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8. For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use antistatic footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks.For personal protection, see section 8. Never use pressure to empty the containers. They are not pressure-resistant containers.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III)::

		Qualifying quant the applic	
Code	Description	Lower-tier requirements	Upper-tier requirements

(in accordance with Regulation (EU) 2015/830)

MAXURETHANE FOAM CAN



Page 5 of 10 Print date: 27/02/2017

Version: 0

Not available.

Revision date: 27/02/2017

P2 FLAMMABLE GASES
7.3 Specific end use(s).

50

10

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
butane (Mixture of isomers)	106-97-8	United	Eight hours	600	1450
butane (Mixture of isoffiers)	100-97-0	Kingdom [1]	Short term	750	1810
	115-10-6	European	Eight hours	1000	1920
directly distant		Union [2]	Short term		
dimethyl ether		United	Eight hours	400	766
		Kingdom [1]	Short term	500	958

[1] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adobted by Health and Safety Executive. [2] According both Binding Occupational Esposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL). The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
alkanes, C14-17, chloro, chlorinated paraffins, C14-17	DNEL	Inhalation, Long-term, Systemic effects	6,7
N. CAS: 85535-85-9	(Workers)		(mg/m³)
N. CE: 287-477-0			
dimethyl ether	DNEL	Inhalation, Long-term, Systemic effects	1894
N. CAS: 115-10-6	(Workers)		(mg/m³)
N. CE: 204-065-8			

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated. DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %			
Uses:	Polyurethane expanding foam for fixing and sealing elements in building			
Breathing protecti	Breathing protection:			
If the recommended	technical measures are observed, no individual protection equipment is necessary.			
Hand protection:	Hand protection:			
If the product is hand	If the product is handled correctly, no individual protection equipment is necessary.			
Eye protection:				
If the product is handled correctly, no individual protection equipment is necessary.				
Skin protection:				
PPE:	Work footwear.			
Characteristics:	«CE» marking, category II.			
CEN standards:	EN ISO 13287, EN 20347			
Maintenance: This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it shoul				
Maintenance.	not be used by other people.			
Observations:	Work footwear for professional use includes protection elements aimed at protecting users against any			
	injury resulting from an accident			

(in accordance with Regulation (EU) 2015/830)

MAXURETHANE FOAM CAN



Version: 0 Revision date: 27/02/2017 Page 6 of 10 Print date: 27/02/2017

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance: Polyurethane foam Colour: N.A./N.A. Odour:N.A./N.A. Odour threshold:N.A./N.A. pH:N.A./N.A. Melting point:N.A./N.A. Boiling Point: N.A./N.A. Flash point: 0 °C Evaporation rate: N.A./N.A. Inflammability (solid, gas): N.A./N.A. Lower Explosive Limit: N.A./N.A. Upper Explosive Limit: N.A./N.A. Vapour pressure: N.A./N.A. Vapour density:N.A./N.A. Relative density:1.3 g/cm³ Solubility:N.A./N.A. Liposolubility: N.A./N.A. Hydrosolubility: N.A./N.A. Partition coefficient (n-octanol/water): N.A./N.A. Auto-ignition temperature: N.A./N.A. Decomposition temperature: N.A./N.A. Viscosity: N.A./N.A. Explosive properties: N.A./N.A. Oxidizing properties: N.A./N.A. N.A./N.A. = Not Available/Not Applicable due to the nature of the product

9.2 Other information.

Pour point: N.A./N.A. Blink: N.A./N.A. Kinematic viscosity: N.A./N.A. N.A./N.A.= Not Available/Not Applicable due to the nature of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT PREPARATION. Splatters in the eyes can cause irritation.

IRRITANT PREPARATION. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness. IRRITANT PREPARATION. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms

(in accordance with Regulation (EU) 2015/830)

MAXURETHANE FOAM CAN



Page 7 of 10 Print date: 27/02/2017

Version: 0 Revision date: 27/02/2017

such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

11.1 Information on toxicological effects.

There are no tested data available on the product.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

a) acute toxicity; Product classified: Acute toxicity (Inhalation), Category 4: Harmful if inhaled.

Acute Toxicity Estimate (ATE): Mixtures: ATE (Oral) = 5.000 mg/kg

b) skin corrosion/irritation; Product classified: Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation; Product classified: Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation; Product classified: Respiratory sensitiser, Category 1: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

e) germ cell mutagenicity; Not conclusive data for classification.

f) carcinogenicity; Product classified: Carcinogen, Category 2: Suspected of causing cancer.

g) reproductive toxicity; Product classified: Effects on or via lactation: May cause harm to breast-fed children.

h) STOT-single exposure; Product classified: Specific target organ toxicity following a single exposure, Category 3:

i) STOT-repeated exposure;
 Product classified:
 Specific target organ toxicity following a repeated exposure, Category 2: May cause damage to organs through prolonged or repeated exposure.

j) aspiration hazard; Not conclusive data for classification.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

12.2 Persistence and degradability.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potencial.

No information is available regarding the bioaccumulation of the substances present.

(in accordance with Regulation (EU) 2015/830)

MAXURETHANE FOAM CAN



Version: 0 Revision date: 27/02/2017 Page 8 of 10 Print date: 27/02/2017

12.4 Mobility in soil.

No information is available about the mobility in soil. The product must not be allowed to go into sewers or waterways. Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13 DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID. Transport documentation: Consignment note and written instructions Sea: Transport by ship: IMDG. Transport documentation: Bill of lading Air: Transport by plane: ICAO/IATA. Transport document: Airway bill.

14.1 UN number.

UN No: UN1950

14.2 UN proper shipping name.

Description: ADR: UN 1950, AEROSOLS, 2.1, (D) IMDG: UN 1950, AEROSOLS, 2.1 (0°C) ICAO (Passenger aircraft): PROHIBITED ICAO (Cargo aircraft): UN 1950, AEROSOLS, 2.1

14.3 Transport hazard class(es).

Class(es): 2

14.4 Packing group.

Packing group: Not applicable.

14.5 Environmental hazards.

Marine pollutant: No

14.6 Special precautions for user.

Labels: 2.1



Hazard number: Not applicable. ADR LQ: 1 L IMDG LQ: 0

(in accordance with Regulation (EU) 2015/830)

MAXURETHANE FOAM CAN



Version: 0 Revision date: 27/02/2017 Page 9 of 10 Print date: 27/02/2017

ICAO LQ: Not applicable.

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR. Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-D,S-U Proceed in accordance with point 6.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC) VOC content (p/p): 30 % VOC content: 390 g/l

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): P2

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

There has been no evaluation a chemical safety assessment of the product.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

tremely flammable gas.

- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H362 May cause harm to breast-fed children.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

Classification codes:

Acute Tox. 4 [Inhalation] : Acute toxicity (Inhalation), Category 4 Acute Tox. 4 [Oral] : Acute toxicity (Oral), Category 4 Aerosol 1 : Flammable aerosol, Category 1 Aquatic Acute 1 : Acute toxicity to the aquatic environment, Category 1 Aquatic Chronic 1 : Chronic effect to the aquatic environment, Category 1 Aquatic Chronic 4 : Chronic effect to the aquatic environment, Category 4 Carc. 2 : Carcinogen, Category 2 Eye Irrit. 2 : Eye irritation, Category 2 Flam. Gas 1 : Flammable gas, Category 1 Lact. : Effects on or via lactation Press. Gas : Gases under pressure Resp. Sens. 1 : Respiratory sensitiser, Category 1

(in accordance with Regulation (EU) 2015/830)

MAXURETHANE FOAM CAN



Page 10 of 10 Print date: 27/02/2017

Version: 0 Revision date: 27/02/2017

STOT RE 2 : Specific target organ toxicity following a repeated exposure, Category 2 STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3 Skin Irrit. 2 : Skin irritant, Category 2

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
- CEN: European Committee for Standardization.
- DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
- DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
- PPE: Personal protection equipment.
- IATA: International Air Transport Association.
- ICAO: International Civil Aviation Organization.
- IMDG: International Maritime Code for Dangerous Goods.
- RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data: http://eur-lex.europa.eu/homepage.html http://echa.europa.eu/ Regulation (EU) 2015/830. Regulation (EC) No 1907/2006. Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.